

ETP407-PU Flexible ducts with polyurethane sheet



Description :

Flexible duct made of 0.40mm thick polyurethane sheet (PU) and galvanized steel (LZ) or copper plated (LR) wire helix.

Characteristics :

Colour: transparent
Temperature range: from -40°C to +90°C (+125°C peaks)
Axial compressibility : 8:1

Size:

Standard 10 meters (20 meters roll up to Ø200 on request).

Use :

- Suction of chips, wood and other material dust, pneumatic conveyance of textile fibres, paper, etc.
- Suction of pharmaceutical ingredients, foodstuff and powder food components.
- Installation in organic/chemical systems.

Peculiar characteristic of this tube is the great resistance to abrasion and cutting (5/6 times greater than rubber and 7 times more than PVC).

Versions :

ETP407-PU-LZ : with galvanized steel wire helix
ETP407-PU-LR : with copper plated steel wire helix

Price list

internal ø	ETP407-PU-LZ	internal ø	ETP407-PU-LZ	internal ø	ETP407-PU-LR	internal ø	ETP407-PU-LR
	euro		euro		euro		euro
40	✓	150	✓	40	✓	150	✓
50	✓	160	✓	50	✓	160	✓
60	✓	170	✓	60	✓	170	✓
63	✓	180	✓	63	✓	180	✓
70	✓	200	✓	70	✓	200	✓
76	✓	225	✓	76	✓	225	✓
80	✓	250	✓	80	✓	250	✓
90	✓	275	✓	90	✓	275	✓
100	✓	300	✓	100	✓	300	✓
110	✓	315	✓	110	✓	315	✓
120	✓	350	✓	120	✓	350	✓
125	✓	400	✓	125	✓	400	✓
130	✓	450	✓	130	✓	450	✓
140	✓	500	✓	140	✓	500	✓