

ETAL Flexible ducts with aluminum/polyester covering



Description

Flexible ducts made of a covering in aluminum/polyester/aluminum and with steel wire helix.

Characteristics

Colour : aluminum.
Temperature range: from -30°C to +140°C (peaks of +180°C).
Radius : 0,6 x Ø.
Air speed : up to 32 m/s.
Pressure : 2500 Pa max.

Size

Standard 10 meters.

Use

- air conditioning;
- ventilation.

Reaction to fire

Italian class: Class 1 (Ministerial Decree 26/06/84).
Euroclasse: B-S1 class, D0 (EN 13501-1:2018)
French class: Class M0 (NF P 92-507: 2004)

Pressure drop

ø interno ETAL														
	82	102	127	152	165	180	203	254	305	318	356	406	457	508
portata m³/h	Pa/m													
40														
50	2,5	0,8												
60	4	1,1												
70	5	1,5												
80	6,5	2	0,7											
90	7,5	2,5	0,9											
100	10	3	1,1	0,5										
200	35	6,5	4	2,7	1,3	0,5								
300		25	8	5	2,5	1,5	0,9							
400		40	16	8	4,5	2,3	1,5							
500			25	14	6,7	3,5	2,3	0,5						
600			33	18	8	5	3	0,9	0,5					
700				25	13	6,5	4,2	1,3	0,7					
800				30	18	7,5	5	1,7	1	0,4				
900				38	20	10	6,5	2	1,3	0,7				
1000					25	13	7,5	2,5	1,5	0,9	0,2			
1500						26	18	5,5	3	1,8	0,8	0,3	0,2	
2000							30	8	5,8	3	1,8	0,8	0,3	0,2
3000								15	10	5	2,8	1,5	0,8	0,5
4000								25	20	8	5	2,8	1,5	0,8
5000									33	18	10	5	2,3	1,3
6000											15	7	3,4	1,9
7000											18	8	4,6	2,6
8000											23	11	5,0	3,4
9000											25	13	8	4,3
10000												17	9,4	5,4
12000													13	7,7
14000													18	10
16000													23	13
18000													30	17
20000														21

Price list

The length of the hose should be considered in a extended position and at environment temperature (16/18°C - tolerance ±2%)

a.r. : price on request

Item normally available from stock			
ø internal	ETAL	ø internal	ETAL
	euro		euro
82	✓	254	✓
102	✓	305	✓
127	✓	318	✓
152	✓	356	✓
165	✓	406	✓
180	✓	457	✓
203	✓	508	✓