

EACLN Connection rings



Description

The collar with overlap is made of Zinc coated (EACLN) or AISI 304BA stainless steel (EACLN-X). This article is used for joining pipes in suction systems.


Characteristics

Material : galvanized steel / stainless steel 304 BA with 5/10 thickness.

Use

The EACLN ring is used for connection and clamping between two pipes in single-wall systems.

It features a clamp-type fastening/closing system with a U-bolt and fully threaded screw with screwdriver slot, allowing secure tightening of the band around the flue duct.



Price List

Diameter	Distance G	Distance H	Distance S	EACLN	EACLN-X
				Eur	Eur
80	6	20	6	3,16	6,18
100	6	20	6	3,16	6,18
120	7	25	8	3,16	6,32
125	7	25	8	3,16	6,32
140	7	25	8	3,16	6,52
150	7	25	8	3,26	6,77
160	7	25	8	3,26	6,77
180	7	25	8	3,38	7,16
200	7	25	8	3,38	7,95
220	7	25	8	3,50	7,95
250	7	25	8	3,94	9,21
280	7	25	8	3,81	9,17
300	7	25	8	4,41	9,61
320	7	25	8	4,71	9,86
350	7	25	8	5,22	10,69
380	7	25	8	5,26	11,18
400	7	25	8	5,56	11,72
450	7	25	8	6,38	12,36