

ETP70-PU Flexible ducts with polyurethane sheet



Description

Flexible ducts made of polyurethane (PU) sheet and copper plated steel wire helix (0,45 mm thickness).

Characteristics

Colour: transparent (blue on request);

Temperature range: from -40°C to +90°C (+125°C peaks);

Axial compressibility: 8:1.

Size

Standard 10 meters (20 meters roll up to Ø200 on request).

Use

- Aspiration of chippings, wood dust and other material;
- Pneumatic transport of textile fibres, paper, etc.;
- Aspiration of pharmaceutical ingredients, foodstuff and powder food components;
- Installation in organic/chemical systems.

Peculiar characteristic of this tube is the great resistance to abrasion and cutting (5/6 times greater than rubber and 7 times more than PVC).

Price List

The length of the hose should be considered in a extended position and at environment temperature (16/18°C - tolerance $\pm 2\%$).

Dimensions are expressed in millimetres (mm).

Prices are quoted per linear metre (m).

Ø Interno	ETP70-PU	Ø Interno	ETP70-PU	Ø Interno	ETP70-PU	Ø Interno	ETP70-PU	Ø Interno	ETP70-PU
	Eur		Eur		Eur		Eur		Eur
40	10,14	90	25,39	130	36,82	180	51,51	350	115,92
50	12,47	100	27,49	140	40,50	200	56,43	400	130,02
60	16,94	110	29,46	150	43,68	250	78,27	450	149,69
70	21,47	120	31,16	160	46,62	275	84,02	500	186,43
80	22,71	125	33,11	170	49,08	300	93,96		