

ETP80-PU-AS Antistatic flexible ducts with polyurethane sheet



Description

Flexible hose made of anti-static polyurethane-ester (60 mm) sheet of polyurethane-ester (Pu) $R \leq 10^8 \Omega$ and copper-plated steel wire spiral.

Characteristics

Color : transparent;

Temperature range : from -40°C to +90°C (+125°C peaks);

Axial compressibility: 3:1.

Size

Standard 10 meters (20 meters roll up to Ø200 on request).

Use

- Suction of chips, wood and other material dust, pneumatic conveyance of textile fibres, paper, etc;
- Suction of pharmaceutical ingredients, foodstuff and powder food components;
- Installation in organic/chemical systems.

Peculiar characteristic of this tube is the great resistance to abrasion and cutting (5/6 times greater than rubber and 7 times more than PVC).

Price list

The length of the hose should be considered in a extended position and at environment temperature (16/18°C - tolerance $\pm 2\%$).

Dimensions are expressed in millimetres (mm).

Prices are quoted per linear metre (m).

Ø Interno	ETP80-PU-AS	Ø Interno	ETP80-PU-AS	Ø Interno	ETP80-PU-AS	Ø Interno	ETP80-PU-AS	Ø Interno	ETP80-PU-AS
	Eur		Eur		Eur		Eur		Eur
40	-	90	-	140	-	200	-	400	-
50	-	100	-	150	-	250	-	500	-
60	-	120	-	160	-	275	-	500	-
70	-	125	-	170	-	300	-		
80	-	130	-	180	-	350	-		