

ETP80-PU-AS Antistatic flexible ducts with polyurethane sheet



Description

Flexible hose made of anti-static polyurethane-ester (60 mm) sheet of polyurethane-ester (Pu) $R \leq 10^8 \Omega$ and copper-plated steel wire spiral.

Characteristics

Color : transparent;

Temperature range : from -40°C to +90°C (+125°C peaks);

Axial compressibility: 3:1.

Size

Standard 10 meters (20 meters roll up to Ø200 on request).

Use

- Suction of chips, wood and other material dust, pneumatic conveyance of textile fibres, paper, etc;
- Suction of pharmaceutical ingredients, foodstuff and powder food components;
- Installation in organic/chemical systems.

Peculiar characteristic of this tube is the great resistance to abrasion and cutting (5/6 times greater than rubber and 7 times more than PVC).

Price list

The length of the hose should to be considered in a extended position and at environment temperature (16/18°C - tolerance $\pm 2\%$).

Dimensions are expressed in millimetres (mm).

Prices are quoted per linear metre (m).

Ø Interno	ETP80-PU-AS	Ø Interno	ETP80-PU-AS	Ø Interno	ETP80-PU-AS	Ø Interno	ETP80-PU-AS	Ø Interno	ETP80-PU-AS
	Eur		Eur		Eur		Eur		Eur
40	15,87	90	31,71	140	48,97	200	68,56	400	160,57
50	19,70	100	33,75	150	52,89	250	96,50	500	184,85
60	22,20	120	37,78	160	56,41	275	103,63	500	230,74
70	26,07	125	40,11	170	59,39	300	115,64		
80	27,54	130	44,53	180	62,35	350	143,02		