

ETP80-PU Flexible ducts with polyurethane sheet



Description

Flexible duct made of polyurethane (PU) sheet and copper plated steel wire helix (0,60 mm thickness).

Characteristics

Colour : transparent (blue or black on request);

Temperature range: from -40°C to +90°C (+125°C peaks); 7

Axial compressibility: 3:1.

Size

Standard 20 meters.

From the diameter 250mm 10 meters.

Use

- Aspiration of chippings, wood and other material dust;
- Pneumatic transport of textile fibres and paper;
- Aspiration of pharmaceutical ingredients, foodstuff and powder food components;
- Installation in organic/chemical systems.

Peculiar characteristic of this tube is the great resistance to abrasion and cutting (5/6 times greater than rubber and 7 times more than PVC).

Price List

The length of the hose should be considered in a extended position and at environment temperature (16/18°C - tolerance $\pm 2\%$).

Dimensions are expressed in millimetres (mm).

Prices are quoted per linear metre (m).

ø Internal	ETP80-PU	ø Internal	ETP80-PU	ø Internal	ETP80-PU	ø Internal	ETP80-PU
	Eur		Eur		Eur		Eur
60	-	140	-	200	-	350	-
80	-	150	-	250	-	400	-
100	-	160	-	275	-	450	-
120	-	180	-	300	-	500	-