

ETS98 Flexible ducts for aggressive fumes



Description

Flexible duct made of polyamide fabric impregnated with santoprene and inner steel wire helix; particularly suitable when operating in presence of aggressive fumes.

Characteristics

Colour : black.

Diameters: from 40 to 500 mm.

Temperature range: from -20°C to +125°C (+ 150°C peaks).

Size

From diameter 40mm to 500mm standard 10 meters (20 meters roll up to Ø200 on request).

For larger diameters minimum lot 10 meters in size of 5 meters.

Use

- Suction of motor vehicle gas;
- Pneumatic conveyance;
- Granule suction;
- Passage of solvents and acids.

Duct particularly suitable when working with aggressive fumes.

Fire reaction

Flame retardant class B1.

Price List

The length of the hose should to be considered in a extended position and at environment temperature (16/18°C - tolerance $\pm 2\%$).

Dimensions are expressed in millimetres (mm).

Prices are quoted per linear metre (m).

Ø Interno	ETS98	Ø Interno	ETS98	Ø Interno	ETS98	Ø Interno	ETS98	Ø Interno	ETS98
	Eur		Eur		Eur		Eur		Eur
40	-	100	-	150	-	275	-	500	-
50	-	110	-	160	-	300	-		
60	-	120	-	180	-	315	-		
70	-	125	-	200	-	350	-		
80	-	130	-	225	-	400	-		
90	-	140	-	250	-	450	-		