

RCS OCS RCK OCK Speed controls



RCS Description

The regulators of the RCS series, suitable for driving fans with single-phase asynchronous motors, make use of particular technical measures to guarantee the best performance in regulation without compromising the optimal functioning of the motor. For the piloting phase, they use an 8-bit microprocessor which constantly follows the sinusoid with the utmost precision, guaranteeing perfect switching of the Triode and therefore optimal motor operation. Filtered according to the CE regulations in force, they make the regulators of this series the most requested by the market.

OCS description

The new line of OCS regulators was created with the aim of providing qualitatively more advanced performances in the field of regulation of ventilation and extraction systems. With the ability to immediately visualize any anomalous situations, it guarantees a better use of the system.

The main innovative features that distinguish this series of products are: "OCS" - "SOFT- START" - "SUR DEMARRAGE" - "LIMITER" - "MACHINE ALARM" - "MIN-MAX SETTING" - "OUTPUT FOR INSTANT AND DELAYED GAS SOLENOID VALVE" - Filtered according to the CE regulations in force.

RCK description

The RCK series controllers are the evolution of the RCS series implemented with a bipolar switch for controlling the neon light that is normally mounted in the hoods for convenience, they also have the following functions: "SOFT-START" - "SUR DEMARRAGE" - "MIN-MAX SETTING" - "OUTPUT FOR CONNECTION TO THE NEON LAMP" - "OUTPUT FOR INSTANT AND DELAYED GAS SOLENOID VALVE" - Filtered according to current CE regulations.

OCK description

Specific regulators for extractor hoods of large kitchens. The OCK series, derived from the OCS series, differs in the addition of a luminous bipolar switch that controls the switching on of the light integrated in the hood.

This series is the most complete of systems for the control and monitoring of the fan in fact it has the following functions: "OCS" - "SOFT-START" - "SUR DEMARRAGE" - "LIMITER" - "MACHINE ALARM" - "MIN-MAX SETTING" - "OUTPUT FOR CONNECTION TO NEON LAMP" - "OUTPUT FOR INSTANT AND DELAYED GAS SOLENOID VALVE" - Filtered according to current CE regulations.

RCS300 - RCS600



RCS900



RCS210 - RCS250



RCK1200



RCK1800



OCS900



OCS1500 - OCS2000



OCK900



OCK1500 - OCK2000



RCS: Operating Data and Price List

Electronic speed controller for fans with single-phase motor.

Models	Technical Data			Price
	Operating Current in Amperes (A)	Maximum Current in Amperes (A)	Protective Fuse (A)	Eur
RCS300	1,5	3	3,15	-
RCS600	3	5	5	-
RCS900	5	7,5	6,3	-
RCS210	7,5	12	10	-
RCS250	12	18	16	-

OCS: Operating Data and Price List

Single-phase manual controller with overload sensor, current limiter and device which ensures the starting of the fan.

Models	Technical Data			Price
	Operating Current in Amperes (A)	Maximum Current in Amperes (A)	Protective Fuse (A)	Eur
OCS900	5	7,5	6,3	-
OCS1500	7,5	12	10	-
OCS2500	12	18	16	-

RCK: Operating Data and Price List

Single-phase manual controller, as RCS series, with switch for neon light.

Models	Technical Data			Price
	Operating Current in Amperes (A)	Maximum Current in Amperes (A)	Protective Fuse (A)	Eur
RCK1200	6	10	8	-
RCK1800	8	13	10	-

OCK: Operating Data and Price List

Single-phase manual controller, as OCS series, with automatic control of the gas valve and switch for neon light.

Models	Technical Data			Price
	Operating Current in Amperes (A)	Maximum Current in Amperes (A)	Protective Fuse (A)	Eur
OCK900	5	7,5		-
OCK1500	7,5	12		-
OCK2500	12	18		-