

EVTT In line fans circular duct for pressure up to 200 Pa



Description

Fans for circular duct, single-phase with 2 speeds. Removable fan motor assembly.

Characteristics

The housing is made of high-quality, durable plastic.

The removable impeller and motor assembly, including the terminal box, is mounted to the housing using spigots and special latch clamps, allowing fast and easy maintenance.

Routine maintenance does not require full disassembly: simply remove the central block from the housing to perform the required servicing.

Use

Designed for supply and exhaust ventilation with airflow capacities from 30 to 1040 m³/h and a static pressure of up to 200 Pa.


Ideal for humid environments such as bathrooms and kitchens, as well as for ventilation of apartments, houses, shops, cafés, etc.

Accessories

Electronic speed regulator RCS 300

Dimensions

All dimensions are in millimeters.

Models		Ø D	B	L	H	Weight
		mm	mm	mm	mm	kg
	EVTT 100	96	167	246	190	1,45
	EVTT 125	123	167	246	190	1,79
	EVTT 125S	123	223	295	250	3,14
	EVTT 150	146	223	295	250	3,19
	EVTT PRO 200	199	239	295,5	261	3,95

Operating Data

dB (A) : noise index to 3 m

Models	Velocity	RPM	Power Input	Current Consumption	Maximum temperature of the transported air	Sound Pressure at 3m	Flow Rate (m³/h)					
		r.p.m.	W	A	°C	dB(A)	0 Pa	40 Pa	80 Pa	100 Pa	150 Pa	200 Pa
EVTT 100	Max.	2385	33	0,21	60	36	187	160	55	30	-	-
	Min.	2180	21	0,11	60	27	145	100	40	15	-	-
EVTT 125	Max.	2455	37	0,27	60	37	280	220	80	50	-	-
	Min.	1950	23	0,18	60	28	220	190	35	-	-	-
EVTT 125S	Max.	2510	54	0,16	60	42	320	275	225	215	150	75
	Min.	1850	28	0,12	60	31	235	190	135	125	65	-
EVTT 150	Max.	2460	60	0,27	60	44	530	470	420	405	270	125
	Min.	1680	30	0,17	60	33	410	360	270	250	80	20
EVTT PRO 200	Max.	2380	108	0,48	60	52	1040	930	850	810	700	580
	Min.	1915	76	0,34	60	45	830	730	680	650	500	350

Price List

Models	Eur
EVTT 100	-
EVTT 125	-
EVTT 125S	-
EVTT 150	-
EVTT PRO 200	-

Speed control

Models	Eur
RCS 300	-