

EVLD Plastic helicoidal aspirator



Description:

Plastic helicoidal aspirator suitable for small environments with particularly careful aesthetics.

Characteristics:

The casing and impeller are made of high-quality, durable ABS plastic with UV protection.

The smart impeller design ensures high fan efficiency and long service life.

Protection rating: IP34.

Use:

Continuous or periodic ventilation of bathrooms, showers, kitchens, and other utility spaces.

Shaft mounting or duct connection.

Compatible with Ø 100, 120, 125, and 150 mm air ducts.

Models :

- EVLD standard.
- EVLDT with timer.

Dimensions

all measurements are in mm

Models		ØD	B	H	L	L1	Peso
		mm	mm	mm	mm	mm	kg
	EVLD-100	100	152	120	126	30	0,6
	EVLD-125	125	177	140	135	34	0,74
	EVLD-150	150	206	165	154	36	0,96
	EVLDT-100	100	152	120	126	30	0,6
	EVLDT-125	125	177	140	135	34	0,74
	EVLDT-150	150	206	165	154	36	0,96

Operating data

T : Timer.

Models	RPM	Power Input	Current Consumption	Sound Pressure at 3m	Airflow (mc/h)									
	r.p.m.	W	A		5 Pa	10 Pa	15 Pa	20 Pa	25 Pa	30 Pa	40 Pa	50 Pa	60 Pa	70 Pa
EVLD-100	2400	14	0,08	33	47	18	1							
EVLD-125	2400	16	0,10	34	175	165	160	155	150	140	55			
EVLD-150	2400	24	0,13	37	265	246	236	227	216	204	157	100	63	31
EVLD-100T	2400	14	0,08	33	47	18	1							
EVLD-125T	2400	16	0,10	34	175	165	160	155	150	140	55			
EVLD-150T	2400	24	0,13	37	265	246	236	227	216	204	157	100	63	31

Price list

Models	Eur
EVLD-100	-
EVLD-125	-
EVLD-150	-
EVLD-100 T	-
EVLD-125 T	-
EVLD-150 T	-