

# ETP407-PU Flexible ducts with polyurethane sheet



## Description :

Flexible duct made of 0.40mm thick polyurethane sheet (PU) and galvanized steel (LZ) or copper plated (LR) wire helix.

## Characteristics :

Colour: transparent  
 Temperature range: from -40°C to +90°C (+125°C peaks)  
 Axial compressibility : 8:1

## Size:

Standard 10 meters (20 meters roll up to Ø200 on request).

## Use :

- Suction of chips, wood and other material dust, pneumatic conveyance of textile fibres, paper, etc.
- Suction of pharmaceutical ingredients, foodstuff and powder food components.
- Installation in organic/chemical systems.

Peculiar characteristic of this tube is the great resistance to abrasion and cutting (5/6 times greater than rubber and 7 times more than PVC).

## Versions :

- ETP407-PU-LZ : with galvanized steel wire helix
- ETP407-PU-LR : with copper plated steel wire helix

## Price list

internal ø	ETP407-PU-LZ	internal ø	ETP407-PU-LZ	internal ø	ETP407-PU-LR	internal ø	ETP407-PU-LR
	euro		euro		euro		euro
40	8,67	150	29,44	40	8,67	150	29,44
50	10,67	160	31,33	50	10,67	160	31,33
60	14,55	170	32,23	60	14,55	170	32,23
63	a.r.	180	39,02	63	a.r.	180	39,02
70	15,89	200	41,77	70	15,89	200	41,77
76	a.r.	225	a.r.	76	a.r.	225	a.r.
80	17,92	250	48,68	80	17,92	250	48,68
90	19,73	275	a.r.	90	19,73	275	a.r.
100	20,87	300	71,46	100	20,87	300	71,46
110	a.r.	315	75,69	110	a.r.	315	75,69
120	24,24	350	84,74	120	24,24	350	84,74
125	25,15	400	98,79	125	25,15	400	98,79
130	25,91	450	122,18	130	25,91	450	122,18
140	27,39	500	134,82	140	27,39	500	134,82