


EVRE Helicoidal fans from ø 250 to ø 450



Description

Helicoidal fans with external rotor motor, fans one-piece printed and net support .

EVRE versione premente



Characteristics

Material: all components are protected against corrosion from the elements.

The motors are IP 44 insulation class B , adjustable .
Finish: polyester powder fans .

Use

Ideal for small ventilations, both civil and industrial .
The quality of materials and excellent compactness make this range of fans very versatile .

Accessories

- Speed regulators;
- Panel square or circular conveyor;
- Flat network side protection fan;
- Overpressure damper.

Operating data

dB (A) : noise index

M : single-phase

T : Three-phase

modello	alimentazione	Portata aria m ³ /h	dB (A)	giri	Potenza Max ass. W
4M 250	230V-1F-50Hz	1060	58	1400	40
4M 300	230V-1F-50Hz	1700	61	1300	90
4T 300	400V-3F-50Hz	1820	64	1350	90
6M 300	230V-1F-50Hz	1160	58	900	45
4M 350	230V-1F-50Hz	2650	60	1320	135
4T 350	400V-3F-50Hz	2750	63	1370	105
6M 350	230V-1F-50Hz	1840	56	880	70
6T 350	400V-3F-50Hz	1820	57	910	55
4M 400	230V-1F-50Hz	2880	65	1300	150
4T 400	400V-3F-50Hz	2900	64	1330	130
6M 400	230V-1F-50Hz	2200	57	860	75
6T 400	400V-3F-50Hz	2290	59	830	70
6M 450	230V-1F-50Hz	3300	57	850	120
6T 450	400V-3F-50Hz	3050	58	850	100

dimensions

all measurements are in mm

modello	distanza D2	distanza H	distanza I	distanza M	modello	distanza D2	distanza H	distanza I	distanza M
4M 250	300	80	45	25	6T 350	422	100	60	30
4M 300	360	90	60	25	4M 400	478	100	60	30
4T 300	360	90	60	25	4T 400	478	100	60	30
6M 300	360	90	60	25	6M 400	478	100	60	30
4M 350	422	100	60	30	6T 400	478	100	60	30
4T 350	422	100	60	30	6M 450	530	120	70	40
6M 350	422	100	60	30	6T 450	530	120	70	40

Price list

modello	ventilatore EVRE ASPIRANTE	ventilatore EVRE PREMENTE	pannello	rete
	euro	euro	euro	euro
4M 250	a.r. ✓	a.r. ✓	-	a.r. ✓
4M 300	a.r. ✓	a.r. ✓	a.r.	a.r. ✓
4T 300	a.r. ✓	a.r. ✓	a.r.	a.r. ✓
6M 300	a.r. ✓	a.r. ✓	a.r.	a.r. ✓
4M 350	a.r. ✓	a.r. ✓	a.r.	a.r. ✓
4T 350	a.r. ✓	a.r. ✓	a.r.	a.r. ✓
6M 350	a.r. ✓	a.r. ✓	a.r.	a.r. ✓
6T 350	a.r. ✓	a.r. ✓	a.r.	a.r. ✓
4M 400	a.r. ✓	a.r. ✓	a.r.	a.r. ✓
4T 400	a.r. ✓	a.r. ✓	a.r.	a.r. ✓
6M 400	a.r. ✓	a.r. ✓	a.r.	a.r. ✓
6T 400	a.r. ✓	a.r. ✓	a.r.	a.r. ✓
6M 450	a.r. ✓	a.r. ✓	a.r.	a.r. ✓
6T 450	a.r. ✓	a.r. ✓	a.r.	a.r. ✓