


EDQV EDQV-PQ Four ways diffusers



Description


4-way square diffusers with removable cones.

Characteristics

Material: aluminium.
Finish: painted white RAL 9016.
Installation: fastening by means of non-visible screws.

Accessories

- SCN galvanised steel regulation damper;
- EPZ-EDQ galvanised steel plenum;
- EPI-EDQ galvanised steel insulated plenum.



Dimensions

all dimensions are expressed in mm

model	EDQV					EDQV-PQ				
	AxA	BxB	CxC	DxD	ExE	AxA	BxB	CxC	DxD	ExE
150x150	140	150	300	50	240	135	145	595	50	235
225x225	215	225	375	50	315	210	220	595	50	310
300x300	290	300	450	50	390	285	295	595	50	385
375x375	365	375	525	50	465	360	370	595	50	460
450x450	435	445	595	50	535	-	-	-	-	-

Operating data


Vk: effective speed (m/s)
m³/h: flow rate
Pa: pressure drops in Pascal
L(m): air throw in metres calculated on ceiling installation, terminal velocity 0.25 m/s
dB(A): noise level

model	effective cross-section m²	Vk (m/s)	3	4	5	6
EDQV 150x150	0,0110	m³/h	119	158	198	238
EDQV-PQ 150x150		L(m)	0,8	1,1	1,4	1,6
		Pa	5	10	16	22
		dB(A)	25	33	38	42
EDQV 225x225	0,0240	m³/h	259	346	432	518
EDQV-PQ 225x225		L(m)	1,1	1,7	2,1	2,5
		Pa	5	13	23	30
		dB(A)	30	39	45	49
EDQV 300x300	0,0380	m³/h	410	547	684	821
EDQV-PQ 300x300		L(m)	1,7	2,2	2,5	3,3
		Pa	7	10	13	23
		dB(A)	35	39	43	48
EDQV 375x375	0,0620	m³/h	670	893	1116	1339
EDQV-PQ 375x375		L(m)	2,0	2,5	3,3	3,9
		Pa	7	12	19	25
		dB(A)	35	41	47	49
EDQV 450x450	0,0850	m³/h	918	1224	1530	1836
		L(m)	2,8	3,8	4,9	5,2
		Pa	7	12	17	25
		dB(A)	36	41	47	49

Galvanised steel regulation damper with blades with opposing movement.



Plenum



EDQV EDQV-PQ	L1 x H1	Ø d	P1	P2	E
150x150	150x150	125	200	245	50
225x225	225x225	150	200	270	50
300x300	300x300	200	200	320	50
375x375	375x375	200	200	320	50
450x450	450x450	250	250	370	50

Price list

Item normally available from stock		
model	Diffusor EDQV	Diffusor EDQV-PQ
	euro	euro
150x150	✓	✓
225x225	✓	✓
300x300	✓	✓
375x375	✓	✓
450x450	✓	-

Accessories

Item normally available from stock						
dimensions LxH	damper SC EDQV	damper SCN EDQV PQ	lateral connection		top connection	
			galvanized plenum	isolated plenum	galvanized plenum	isolated plenum
			EPZ-EDQ	EPI-EDQ	EPZ-EDQ	EPI-EDQ
	euro	euro	euro	euro	euro	euro
150x150	✓	✓	✓	✓	✓	✓
225x225	✓	✓	✓	✓	✓	✓
300x300	✓	✓	✓	✓	✓	✓
375x375	✓	✓	✓	✓	✓	✓
450x450	✓	-	✓	✓	✓	✓