

ETP70-PU Flexible ducts with polyurethane sheet



Description :

Flexible ducts made of polyurethane (PU) sheet and copper plated steel wire helix (0,45 mm thickness).

Characteristics :

Colour: transparent (blue on request)
Temperature range: from -40°C to +90°C (+125°C peaks)
Axial compressibility : 8:1

Size:

Standard 10 meters (20 meters roll up to Ø200 on request).

Use :

- Aspiration of chippings, wood dust and other material
- pneumatic transport of textile fibres, paper, etc.
- Aspiration of pharmaceutical ingredients, foodstuff and powder food components.
- Installation in organic/chemical systems.

Peculiar characteristic of this tube is the great resistance to abrasion and cutting (5/6 times greater than rubber and 7 times more than PVC).

Price list

The length of the hose should to be considered in a extended position and at environment temperature (16/18°C - tolerance ±2%)

Item normally available from stock

internal ø	ETP70-PU	internal ø	ETP70-PU	internal ø	ETP70-PU	internal ø	ETP70-PU	internal ø	ETP70-PU
	euro		euro		euro		euro		euro
40	✓	90	✓	140	✓	225	✓	450	✓
50	✓	100	✓	150	✓	250	✓	500	✓
60	✓	110	✓	160	✓	275	✓		
70	✓	120	✓	170	✓	300	✓		
75	✓	125	✓	180	✓	350	✓		
80	✓	130	✓	200	✓	400	✓		