



Description

Flexible pipes made from a multilayer aluminium (90%) / polyester (10%) strip, supported by a harmonic steel wire. The insulating mat, made of glass wool, density 16kg/m³, thickness 25 mm, is protected externally by an anti-condensation sleeve.

Characteristics

Colour of inner tube: grey.
Colour of outer sheath: aluminium.
Production diameters: 80 to 610 mm.
Inner tube thickness: 150 micron.
Thickness of anti-condensation protection: 50 micron.
Temperature range: -20 to +250°C.
Bending radius: 06 x Ø.
Max. air speed: 32 m/s
Max. working pressure: 3000 Pa

Size

Standard 10 meters.

Use

-Air conditioning.
Mechanical ventilation.
To reduce the formation of condensation and heat dispersions.

Reaction to fire

Certified Class 0, it meets the high regulatory requirements for fire protection.

Price list

The length of the hose should be considered in a extended position and at environment temperature (16/18°C - tolerance ±2%)

Item normally available from stock			
internal Ø	ETF0-Therm	internal Ø	ETF0-Therm
	euro		euro
80	✓	315	✓
102	✓	356	✓
127	✓	406	✓
152	✓	457	✓
162	✓	508	✓
203	✓	560	✓
254	✓	610	✓
305	✓		