

ETP80-PU-AS Antistatic flexible ducts with polyurethane sheet



Description :

Flexible hose made of anti-static polyurethane-ester (60 mm) sheet of polyurethane-ester (Pu) $R \leq 10 \wedge 8 \Omega$ and copper-plated steel wire spiral.

Characteristics :

Color : transparent
Temperature range : from -40°C to +90°C (+125°C peaks)
Axial compressibility : 3:1

Size:

Standard 10 meters (20 meters roll up to Ø200 on request).

Use :

- Suction of chips, wood and other material dust, pneumatic conveyance of textile fibres, paper, etc.
- Suction of pharmaceutical ingredients, foodstuff and powder food components.
- Installation in organic/chemical systems.

Peculiar characteristic of this tube is the great resistance to abrasion and cutting (5/6 times greater than rubber and 7 times more than PVC).

Price list

The length of the hose should to be considered in a extended position and at environment temperature (16/18°C - tolerance ±2%)

internal ø	ETP80-PU-AS	internal ø	ETP80-PU-AS	internal ø	ETP80-PU-AS	internal ø	ETP80-PU-AS	internal ø	ETP80-PU-AS
	euro		euro		euro		euro		euro
40	✓	90	✓	140	✓	225	✓	450	✓
50	✓	100	✓	150	✓	250	✓	500	✓
60	✓	110	✓	160	✓	275	✓		
70	✓	120	✓	170	✓	300	✓		
75	✓	125	✓	180	✓	350	✓		
80	✓	130	✓	200	✓	400	✓		